



### Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Relay discrete output module
Discrete output number	32 screw terminal block
Contacts type and composition	NO

### Complementary

Output voltage limits	19...264 V AC 10...34 V DC
[I <sub>th</sub> ] conventional free air thermal current	2 A
Power consumption in VA	50 VA 24 V AC-12 resistive 24 VA 24 V AC-15 inductive 100 VA 48 V AC-12 resistive 200 VA 110...120 V AC-12 resistive 200 VA 200...240 V AC-12 resistive 50 VA 48 V AC-15 inductive 50 VA 110...120 V AC-15 inductive 50 VA 200...240 V AC-15 inductive
Power consumption in W	24 V DC-12 resistive 24 V DC-13 inductive
Response time	< 10 ms
Current consumption	175 mA
Power dissipation in W	3.5 W
Isolation voltage	1500 V 1 s
Insulation resistance	>= 10 mOhm

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0919 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------

Pre-Actuators/Outputs Connections

Wiring Diagram

